

Technical datasheet

Woodkeeper Ezee Hand Polish

Product description

It is a single pack wood polish system specially design for application by means of cloth using hand to give a smooth glossy finish. It can be used on all types of wood & veneer.

Performance benefits:

- A quick drying solvent base wood polish with high transparency & excellent applicability.
- It is design to improve the warm tones on wood, conscientious building up of properly filled surface to produce an elegant glossy finish.
- Low odour
- It has good scratch resistance and holds value for money
- No added lead, mercury and chromium.

Recommended use

Applicable for interior finishing of furniture's, wooden crafts, MDF boards, veneers, plywood etc.

Technical Data (Typical Indicative values)

Viscosity @300C, B4 Cup	15±5 Sec
Specific Gravity, gm/Lt	0.83 ± 0.02
Surface dry	< 15 Min
Shelf Life in months for the originally packed tightly closed condition maintained at 250 C	12

Recommended Application

Sand the seasoned wooden surface using emery paper (180) along the grains followed by 320 or 400. Wipes off the loose dust particles. Fill the wood grains using Berger NC Sanding Sealer(A09990) – Dilution 1:1 with NC Thinner & application with a soaked cloth (ensuring the cloth is a clean, white, soft muslin cloth & not dyed) in a circular motion & then evening up with strokes along the grains. Minimum 4 coats with intervals of at least 30 minutes to 1 hour and sand the intermediate coats using appropriate grit emery paper depending upon the preferred finish.

Page 1 of 2

Issue date: 17/12/2022

Apply several coats of Ezee hand polish with 15-30 minutes coating time intervals along the grains in one direction only using lint free cloth until desired finish is achieve. Sanding between coats of Ezee hand polish may or may not require depending upon the preferred finish

Pack Size

Berger Woodkeeper Ezee hand Polish-(0FY0Z2): 500 ml, 1L, 5 L.

Storage & Handling

1.	Storage	Store in cool and dry place. Keep away from source of ignition. Keep container tightly closed, Keep out of children reach and away from food.
2.	Disposal	Do not pour left over product down the drain or any water course. Dispose in accordance with local regulation.
3.	Flash Point	Above 120C (Abel Closed Cup)

SAFETY INFORMATION

1.	Fire hazard Class	Flammable
2.	Safety Precaution	Kindly refer to the MSDS for Berger Woodkeeper Ezee hand Polish. Ensure good ventilation during storage, application & drying of product. Wear protective clothes & gloves. Smoking is prohibited while painting. A suitable dust nose pad should be worn when rubbing the surface. Avoid inhaling the vapour. Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.
	DISCLAMER	The information contained within this data sheet is based on information believed to be reliable at the time of its preparation. The company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user and the data contained herein. No guarantee of results is implied since conditions of use are beyond our control. Products undergo continuous improvement. The technical data in this catalogue are therefore subjected to change.

Page 2 of 2

Issue date: 17/12/2022