

WEATHERCOAT ANTI DUSTT

PREMIUM EXTERIOR EMULSION



Product Attributes



Dust Guard

Exceptional dust resistance keeps your walls sparkling clean

No black streaks

Walls are free from stains and black streak marks caused by dust deposition



Anti-algae & Anti-fungal protection

Provides long-lasting protection against fungus and algae on the walls

Rich Soft sheen

Rich, soft sheen finish enhances the beauty of the house



Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future.

Product Description

WeatherCoat Anti Dustt is a high-performance paint with rich, soft sheen. It is formulated with special grade of acrylic emulsion and additives. The paint has unique dust repelling properties owing to the presence of Dust Guard Technology. It is also resistant to chalking, flaking, fading, algae and fungal growth. Walls painted with WeatherCoat Anti Dustt retains the look of the paint for a long time compared to conventional exterior paint.

Recommended Use

Exterior plastered surfaces and concrete blocks

Colour Range



Over 2,000 shades

Finish

VERY HIGH

HIGH

MEDIUM

RICH SOFT SHEEN ✓

Rich Soft sheen

Toxicity



VOC - < 50 gm/ltr

Coverage

60 -65 sq.ft/ lt/2 coats, under ideal test conditions.
(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/plastered surfaces - WeatherCoat Exterior Primer / Seal-O-Prime. Alternatively use WeatherCoat All Guard by diluting 1L of emulsion in 1L of water.

Putty: For wall/ plastered surfaces - Bison Wall Putty

Recommended Surface

Sand, cement plaster, asbestos, brickwork, concrete block and fiberboards

Drying Time



SD: 25-35 min depending on weather conditions

HD: 4-6 hours

Gloss Level



5-8 at 60° GH when released

Application Method



Brush / Roller / Spray

Recommended Thinner / Cleaner



Potable water

Dilution Ratio



Brush: 400 ml of water/1L emulsion

Dilution of dark shades only



Maximum dilution should be 10 - 15 % depending on shade. Coverage may be less compared to light shades.

WEATHERCOAT ANTI DUSTT

PREMIUM EXTERIOR EMULSION



Packs



ColorBank/ Non-ColorBank – Pack
0.9, 1, 3.6, 4, 9, 10 and 20 L

Bases

PO, W1, N, N1, N2, Ivory, Yellow and Brown



Fire Hazard Class
Non-flammable



Pot Life of Thinned Material
Overnight

Surface Preparation




For fresh/new surfaces: Strip all loose particles from the surface with wire brushing and by scraping, followed by a wipe down. Wash the surface down with water and allow it to dry.



Apply 1 or 2 coats of Berger Bio-Wash solution (5%v/v) and allow it to dry overnight.



Wash it again the next day with potable water. Allow the surface to dry fully.



Apply one coat of primer and allow it to dry for 6 – 8 hours.

For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces or damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/05/2023. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com