



Product Attributes

**Better Hiding
Than Local
Emulsion**



Matt Finish

**Green Pro
Certified**
Validates our
effort in
striving towards
cleaner, more
sustainable future.



BISON LITE

ACRYLIC INTERIOR EMULSION



Product Description

Bison Lite is an acrylic emulsion based paint that gives a uniform matt finish to the walls. It is the most affordable interior emulsion and can be tinted to 1000+ shades through ColourBank or universal stainers. It is strictly for application on interior walls only.

Recommended Use

Plastered surfaces, concrete, asbestos sheet and false ceilings.

Colour Range



Over 2,000 shades

Coverage



Approx. 80 -90 sq.ft/ lt/2 coats, on well- prepared, primed surface.
(Actual coverage may vary depending upon surface conditions, preparation, application and type of shade)

Recommended Thinner / Cleaner



Potable water

Drying Time (at 60 % RH, 25° C)



SD: 15 minutes
HD: 6 - 8 hours

Recommended Dilution



50 - 65 % by weight

Gloss Level



Matt, no sheen

Application Method



Brush/ Roller/ Spray



BISON LITE

ACRYLIC INTERIOR EMULSION



Packs



Flash Point

Water- based paint, non-flammable



Pot Life of Thinned Material

Use within 24 hours



Shelf life

2 years from date of manufacturing
in unopened containers kept in
cool, dry place away from sunlight.

Surface Preparation



Remove paint, dirt,
loose particles
from the surface
to be painted using
wire mesh.



Fill up minor cracks with acrylic
putty (Happy Wall Putty).
Cracks which are larger than 5mm
should be filled with cement
work. Let it dry completely

Priming:



Apply two coats of primer (BP White Primer suitably
diluted) leaving at least 6-8 hours between coats.
Application of Primer is mandatory

Directions for Topcoat Application

- Apply Bison Lite after recommended dilution with potable water.
- Apply topcoat with brush/ roller.
- Allow the paint to dry for 6-8 hours and then apply the 2nd coat.
- Very light shades may require more than two coats for best performance.

PRECAUTIONS

- Stir well and strain the diluted paint before use
- Do not over dilute or over extend brush
- Do not apply paint if the ambient temperature is less than or expected to fall below 10° C
- Use only Berger Paints machine colourants to tint shades
- Allow sufficient time for each coat to dry before next coat application
- Apply paint with Auto- roller for best performance

Version No: BPP1/10/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com