



SILK GLAMOR

CRYSTAL REFLECTIVE TECHNOLOGY



Product Attributes

Water repellent



Flexible enough to cover hair-line cracks

High opacity



High coverage

Low smell




Product Description

Silk Glamor Luxury Emulsion is a premier interior wall paint designed to give walls a premium and rich appearance. It is formulated with tailor-made 100% acrylic emulsion, which makes it durable and retains fresh, new glossy look for a longer period of time. Silk Glamor comes in a range of regular and metallic bases, shades, which can be combined to give a premium look to the interiors.

Recommended Use

Plastered surfaces, concrete walls, fiberboards, asbestos, gypsum boards and false ceilings.

Colour Range



Over 2,000 shades

Finish



Premium, rich and glossy look

Toxicity



VOC - 40 - 50 gm./L
No added lead, chromium or mercury

Coverage

Approx.150 - 170 sq.ft/ lt/2 coats, under ideal test conditions. (Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: Silk Luxury Basecoat

Putty: For wall/ plastered surfaces – Bison Wall Putty/ Happy Wall Putty

Gloss Level



60° = 13 - 15;
85° = 45 - 55(Depending on shade, measured as per standard test method)

Anti - fungal



Resists growth of algae, fungus and moulds

Drying Time



SD: 15 -25 min at 60% RH , 25° C
HD: 6 - 8 hours

Application Method



Brush/ Roller/ Spray

Dilution Ratio



Brush: 40 -50% by volume
Roller: 25 - 30% by volume
Deep shades from N base to be applied without dilution

Recommended Thinner / Cleaner



Potable water



SILK GLAMOR

CRYSTAL REFLECTIVE TECHNOLOGY



Packs



1 Ltr

4 Ltr

10 Ltr

20 Ltr

ColorBank

Pack of 0.9, 3.6, 9 & 18 L

Bases

W1, N, N2, Yellow & Red



Fire Hazard Class
Non- flammable



Pot Life of Thinned Material
Overnight

Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.



Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty / cement to dry.



Apply the first coat of primer and allow it to dry for 6 - 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 - 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.

For Previously Painted Surfaces: Strip the old paint as far as possible. Roughen the unremoved portion with no 180 or no 220 emery paper. Remove all loosely adhering particles or dust.

Directions for Application

For topcoat, dilute the paint as per the recommended dilution ratio. Apply the first finishing coat with brush or roller and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Cleaning Instructions

Use only toilet soap to clean stains

To clean oil-based stains, use mineral turpentine oil only

Use only a soft white cotton cloth for cleaning

While cleaning, wipe gently without using pressure

Attempt cleaning the surface only after one month of application

Points to Note

- ▶ Shake well before use
- ▶ Do not over dilute.
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio - Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help
- ▶ Do not apply paint when ambient temperature is below 10° C or above 45° C

Version No: BPP1/04/2022. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com