

SILK GLAMOR MATT LUXURY EMULSION



Product Description

Silk Glamor Matt Luxury Emulsion is an interior wall paint designed to give your walls a durable premium, matt appearance. It is formulated with 100% acrylic emulsions that forms gives smooth finish to your walls. The product is resistant to fungal growth and film retains the fresh new look longer.

Areas of Application

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling

Technical Parameters



Coverage

150-170 sqft/lt/2 coats depending on shade, quality of surface preparation and application condition

Surface Dry 15-25 min at 60% RH, 25°C Hard Dry





6-8 hours

Stability of used paint
Use within 24 hours









Application Tools



Brush & Roller

Recommended Dilution



Brush: 40% by volume **Roller:** 35 – 50% by volume Deep shades from N2 base may not require dilution.

Application Details



Surface Preparation

Remove all dirt, loose paint, flakes using wire mesh. Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty/cement work to dry.



Priming

Apply one coat of Silk Luxury Base Coat suitably diluted and dry it overnight



Top Coat

Mix well. Dilute with potable water and apply with brush or roller. Allow it to dry for at least 6-8 hours or overnight depending ambient temperature, humidity and surface conditions. Do not over thin. Apply second coat only when the first coat is dry.

Do not overthin. Do not apply when ambient temperature is below 10°C or more than 40°C

Safety Data: Refer MSDS

Additional Information: No added lead, Chromium (VI), Mercury

Version No: BPP1/10/2022. Please note that this data sheet supersedes all previous versions.