



BISON GLOW+

INTERIOR ACRYLIC EMULSION



Product Attributes

4 Years
Warranty



Sheen Finish
Imparts
sheen finish
to the walls



Smooth Finish



**Resistant
to Chalking
& Fading**



Green Pro Certified
Validates our effort
in striving towards
cleaner, more
sustainable future



Product Description

Bison Glow+ Emulsion is a water-based interior wall paint that provides a smooth, durable, soft sheen finish at an affordable price. It is an excellent upgrade from the regular Bison variant.

Recommended Use

Plastered surfaces, concrete walls, asbestos, fiberboard, gypsum board and false ceilings.

Colour Range



Over 2000 shades

Finish



Toxicity



VOC :35 gm/lit Max.
for Whites and Bases

Recommended Undercoats

Primer: For wall / plastered surfaces – BP Cement Primer WT (Alkali Resistant)

Putty: For wall / plastered surfaces – Bison Wall Putty / Happy Wall Putty

Coverage



120-130 sqft/lit/2 coats, under ideal
test conditions (Actual coverage may vary
depending upon surface conditions,
preparation, application and type of shade)

Recommended Dilution



Brush : 50 – 60% by volume
Roller : 45 – 55 % by volume
Auto Roller : 45 – 55 % by volume

Application Method



Brush / Roller / Spray

Recommended Thinner / Cleaner



Potable water

Gloss Level



4 -7 at 60 ° GH (depends on shade)
measured as per standard method

Drying Time



SD: 15 – 25 minutes at 60 % RH, 25°C
HD: 6 – 8 hours



BISON GLOW+

INTERIOR ACRYLIC EMULSION



Packs



1 Ltr 4 Ltr 10 Ltr 20 Ltr



Fire Hazard Class

Water- based paint,
non-flammable



Pot Life of Thinned Material

Use within 24 hours

Surface Preparation




For fresh / new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.

For Previously Painted Surfaces: Strip all the old paint and remove all the loose particles before starting the above process of primer and putty application.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Cleaning Instructions

Use only toilet soap to clean stains

Use only a soft white cotton cloth for cleaning

While cleaning, wipe gently without using pressure

Attempt cleaning the surface only after one week of application

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use one coat of Bio – Wash for killing fungal growth
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ For deep shade. apply one additional coat
- ▶ Do not apply paint on lime washed surfaces and damp wall
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/03/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com