

# WALMASTA

## ADVANCED



### Product Attributes



4 Years  
Warranty

Resistant  
to Chalking  
& Fading



Prevents  
Algal Fungal  
Groth

Better  
alternative to  
cement paints



Green Pro Certified  
Validates our effort  
in strivin ore  
sustainable future




### Product Description

Walस्ता Advanced is water-based acrylic exterior emulsion that is ideal for dry climates, resists chalking, flaking and prevents algal/fungal growth. It offers a smooth matt finish.

### Recommended Use

Exterior plastered surfaces, asbestos, concrete blocks, fiberboards.

#### Colour Range



Over 2,000 shades

#### Finish

HIGH

MEDIUM

SMOOTH

MATT ✓

#### Toxicity



VOC <50 gm/lt  
No added Lead, Arsenic,  
Chromium (VI) and Mercury

### Coverage

55 -60 sq.ft/ lt/2 coats, under ideal test conditions.

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

### Recommended Undercoats

**Primer:** For wall / plastered surfaces – Walस्ता Primer/BP Exterior Primer  
Alternatively, Walस्ता diluted using 1 L of water with 1 L of emulsion may be used

**Putty:** For wall / plastered surfaces – Bison Wall Putty


#### Drying Time



**SD:** 25-35 min depending on weather  
conditions

**HD:** 4 - 6 hours

#### Application Method



Brush / Roller / Spray

#### Dilution Ratio



**Brush:** 600 ml of water/1L emulsion  
In case of N Base shades, no dilution is  
advised to ensure proper colour depth

**For dark shades only:** Maximum  
dilution should be 10 – 15 % depending  
on shade. Coverage may be less  
compared to light shades.

#### Recommended Thinner



Potable water

# WALMASTA

## ADVANCED



## Packs



**ColorBank / Non- ColorBank**  
Pack of 1, 4, 10 and 20 L

**Bases**  
PO, W1, N, N1, N2 and Cream



**Fire Hazard Class**  
Non- flammable



**Pot Life of Thinned Material**  
Overnight

## Surface Preparation

### For New Masonry Surfaces



The surface should be allowed to cure completely.  
Apply one coat of Illusion Sealer to avoid salt petering.

### For Previously Painted Surfaces



Ensure the surface is free from all loose paints, dust particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe or scrub it clean by wire brushing.



Cracks, holes, dents or damp areas should be repaired properly before painting.



If required, treat the surface with Bio-wash solution, and wash it next day with potable water and let the surface dry completely.

## Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 - 8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

### Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

### Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces or damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/03/2025. Please note that this data sheet supersedes all previous versions.

## BERGER PAINTS INDIA LIMITED

**Berger House**, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com