

WALMASTA GLOW+




Product Attributes

4 Years
Warranty



Sheen Finish
Imparts sheen finish to the walls

Resistant to Chalking & Fading



Prevents Fungi & Algae Growth

Green Pro Certified
Validates our effort in striving towards cleaner, more sustainable future



Product Description

Walस्ता Glow+ is a water-based acrylic exterior paint that delivers a soft sheen finish at an affordable price. Ideal for dry climates, it resists chalking and flaking while preventing algal and fungal growth.

Recommended Use

Sand/cement plaster, asbestos, brickwork and concrete blocks

Note: Not recommended on lime wash

Colour Range



Over 2,000 shades

Finish



Toxicity



VOC <50 gm/lit
No added Lead, Arsenic, Chromium (VI) and Mercury

Recommended Undercoats

Primer: For wall / plastered surfaces – Walस्ता Primer or BP Exterior Primer

Drying Time



SD: 30 minutes
(depending on weather conditions)
HD: 4 - 6 hours

Dilution



50 - 60% by volume with water
For darker shades: 0 - 10%

Recommended Thinner



Potable water

Gloss Level



3 - 6 at 60 ° GH (depends on shade)
measured as per standard method

Over Coating Interval



4 - 6 hours

Coverage



Approx. 60 - 65 sq.ft / lt/2 coats,
under ideal test conditions.
(Actual coverage may vary depending upon surface conditions, preparation and type of shade)

Application Method



Brush / Roller / Spray

WALMASTA GLOW+



Packs



Fire Hazard Class
Non- flammable



Pot Life of Thinned Material
Use within 24 hours

Surface Preparation

For New Masonry Surfaces



The surface should be allowed to cure completely.
Apply one coat of Illusion Sealer to avoid salt petering.

For Previously Painted Surfaces



Ensure the surface is free from all loose paints, dust particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe or scrub it clean by wire brushing.



Cracks, holes, dents or damp areas should be repaired properly before painting.



If required, treat the surface with Bio-wash solution, and wash it next day with potable water and let the surface dry completely.

Priming:



Apply 1- 2 coats of Walस्ता Primer or BP Exterior Primer.

Directions for Application

Dilute the paint as per the recommended dilution ratio. Apply 2-3 coats of Walस्ता Glow topcoat paint with 4 – 6 hours of interval.

Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Scrape off old paint thoroughly before painting starts
- ▶ Gyro shake well after tinting through CB Machine
- ▶ Do not apply paint on lime washed surfaces or damp wall
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/03/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com