

LUXOL METALLICS



Product Attributes

Metallic
sheen



PU
Enriched

Extra
Hiding



Higher
Viscosity

4 YEARS
WARRANTY



Green Pro
Certified

Product Description

Luxol Metallics offers a lustrous metallic finish that can be used for both exterior and interior surfaces, mainly on mild steel, wooden, and suitably prepared masonry surfaces. Formulated with specially designed proprietary polyurethane resins, it provides a long-lasting sheen with superior coverage.

Recommended Use

Area of application:



Metal



Wood



Masonry

Suitable for:



Interior & Exterior

Colour Range



Gold, Silver, Copper

Recommended Dilution



Can be diluted with Berger
Thinner (800/T65/03E)
with 8-10% dilution (V/V)

Application Method



Brush, Roller & Spray

Flash Point



Above 30°C
(Abel Closed Cup)

Drying Time



SD : 4 - 5 hrs | HD : 24 hrs
depending on weather & surface condition
Over coating preferably overnight.

Finish



Coverage



1 COAT: 200-250 sq.ft/Lt*
2 COAT: 100-120 sq.ft/Lt*

(*Actual coverage may vary from the theoretical coverage
due to factors such as method and condition of application,
surface roughness, porosity and thickness of the film.)

Viscosity



120-140 sec @ 30°C./Ford Cup B-4

Gloss Level



Metallic Luster Finish

Recoating Period



Overnight drying, after applying
first coat (Depending upon ambient
temperature & humidity)

LUXOL METALLICS



Packs Available



Stability Of Thinned Paint
To be used within 24 Hours



Fire Hazard Class
Flammable



Shelf Life

24 months from the date of manufacture when stored in a properly sealed container at room temperature below 30°C and away from direct sunlight

Surface Preparation

Surface Inspection :



Before painting, undertake repair of all surface imperfection, cracks, leakages, undulation.

Scrapping :



Remove all loose paint, dirt, fungus, algae, moss and salt deposits by sanding the surface with Berger Sand Paper or alternatively by Berger Express Painting Sander with Paint Scraper attachment.

Crack Bridging :



For filling cracks up to 5mm use Home Shield Crack Fill Paste. For wider cracks use Home Shield Advance Latex Plus as per the product usage guidelines. Use Woodkeeper Fill-O-Dent to fill the cracks

Waterproofing :



If required, apply Home Shield Latex Shield 2K on the affected areas as per the product usage guidelines. For highly affected areas Home Shield DampStop coating system is recommended.

Putty Application :



Apply 1 or 2 Coats of Putty at an interval of 4-6 hours.

Recommended Putty :

Walls : Bison Wall Putty/HS Water Proof Putty
Metal & Wood : Luxol Knifing Putty

Primer Application :



Apply 1 or 2 coats of primer as per recommended time interval and dilution.

Recommended Primers :

Walls : BP Cement Primer ST
Ferrous Surface : Luxol QD 1K Epoxy Primer/BP Anti Corrosive 1K Epoxy Primer
Galvanized Steel : Bison Wash Primer followed by Luxol QD 1K Epoxy Primer/BP Anti Corrosive 1K Epoxy Primer
Wood : Parrot Wood Primer

Top coat :



Apply 2 coats of Luxol Metallics with recommended dilution ratio as finish coat. Apply second coat after 24 hours of applying first coat.

Special Note :

- Moisture content of the wall should be below 12%.
- pH value of the wall surface should be between 7 - 11.

Storage :

- Store in a cool dry place.
- Keep away from source of ignition.
- Keep container tightly closed, out of children's reach and away from foodstuff.

Disposal :

- Do not pour left over Putty / Primer / Top Coat down the drain or any watercourse.
- Dispose in accordance with local regulation.

Safety & Precaution

- Ensure good ventilation during application and drying of paint.
- Wear protective clothes and gloves.
- Smoking is prohibited while painting.
- Avoid inhaling the vapour. Wear suitable dust nose pad when rubbing the surface.
- Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.

Version No: BPP1/06/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 • CONSUMER RELATIONS MANAGER • Ph : 1800-103-6030
SMS BERGER to 56767 • Email : consumerfeedback@bergerindia.com • www.bergerpaints.com
Corporate Office : Plot No. : CF - 4 • Premises No. : 02-0173 • Action Area - IC • New Town • Kolkata 700 156