

# KOLOR PLUS

## Interior Premium Emulsion



### Features



**Color Guard Technology**

**Anti-Fungal**



**Washable**

**Rich, Smooth Finish**



**6 years of Warranty**

**High Coverage/  
High Opacity**



### Product Description

Kolor Plus, is a premium interior emulsion backed by European technology, designed to keep your walls looking fresh and vibrant for years. Its advanced Colour Guard Technology ensures superior color retention and a rich, smooth finish with minimum spattering. Its washable feature keeps walls fresh wash after wash.

### Recommended Use

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling.



### Coverage

120-140 sqft/ltr/2 coats depending on shade, quality of surface preparation and application condition.



### VOC

5 gm/l (max)



### Recommended Dilution

**Brush application:** 50% by volume.  
**Auto-roller/ spray:** 50% by volume.  
Deep shades from the N2 base are to be applied without dilution



### Drying Time

Surface Dry: 15-25 min at 60% RH, 25°C Hard Dry: 6-8 hours



### Gloss/Sheen

Matt

# KOLOR PLUS

## Interior Premium Emulsion



### Packs



1 Ltr

4 Ltr

10 Ltr

20 Ltr



### Stability of Used Paint

Use within 24 hrs

### Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean. Apply one coat of bio-wash after cleaning fungal / algal growth.



Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty / cement to dry.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.



#### For Previously Painted Surfaces

Strip the old paint as far as possible. Roughen the unremoved portion with no 180 or no 220 emery paper. Remove all loosely adhering particles or dust.



### Directions for Application

For topcoat, dilute the paint as per the recommended dilution ratio. Apply the first finishing coat with brush or roller and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

### Points to Note

- Shake well before use
- Do not over dilute.
- Keep the container tightly closed to prevent drying
- Use one coat of Bio – Wash for killing fungal growth
- Scrape off old paint thoroughly before painting starts
- Gyro shake well after tinting through CB Machine
- For deep shade apply one additional coat
- Do not apply paint on lime washed surfaces and damp wall
- In case of contact with eyes, wash immediately with water and seek medical help
- Do not apply paint when ambient temperature is below 10°C or above 45°C

Version No: BPP1/07/2025. Please note that this data sheet supersedes all previous versions.

### BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: [consumerfeedback@bergerindia.com](mailto:consumerfeedback@bergerindia.com) | [www.bergerpaints.com](http://www.bergerpaints.com)