

PLATINA BISON PLUS INTERIOR PUTTY



Product Attributes

Superior Whiteness



Super Smooth Finish

Easy to Use



No Curing Required



Eco-friendly



Green Pro Certified

Product Description

Platina Bison Plus Interior Putty is a high-quality polymer and white cement-based powder putty with extra whiteness, specially designed for interior walls and ceilings. It provides a smooth and flawless finish eliminating surface undulations and imperfections, making it ideal for achieving a perfect base for painting or further finishing touches.

Recommended Surface

Area of application:




Sand/Cement/
Gypsum Plaster



Concrete



Asbestos




Mivan
Surface

Suitable for :



For Interior only

Colour Range



White

Finish

SMOOTH ✓

MEDIUM

HIGH

MATT

Recommended Dilution



Can be diluted with
34-36% Water / Volume of Putty
by using Mechanical Stirrer
at least 10 minutes prior to application

Coverage



2 COATS : 7-8 sq.ft/Kg*

(*Depending upon the conditions of the substrate, thickness of putty layer, application skill.)

Recommended Thinner



Potable Water

Drying Time



SD : 45 Mins - 60 Mins

HD : Overnight

(Depending on weather conditions, thickness of putty layer, application skill)

Application Tools



Putty knife/trowel



HC 950

PLATINA BISON PLUS INTERIOR PUTTY



Packs Available



40 KG



Stability Of Thinned Paint

To be used within 2 Hours



Fire Hazard Class

Non-Flammable



Shelf Life

12 months from date of manufacture as long as the bag is sealed and kept at normal temperature in a cool and dry place.

Direction to Use

SURFACE PREPARATION :



Remove all loose, flaky, chalky substances from the wall by wire brushing or by using Berger Sand / Wet & Dry Sheets 220 and clean the surface with water and allow the surface to dry.

MIXING :



Add 34-36% water by volume to the putty and mix thoroughly using mechanical stirrer to get a homogeneous paste. Allow the mixture to stand for atleast 10 minutes prior to application.

APPLICATION PROCESS :



- 1 Pre-wet the wall surface with clean water before application of the 1st coat.
- 2 Apply 1st coat of Bison Plus Putty with a putty knife / trowel by drawing from bottom to top. Apply the 2nd coat after an interval of 1 day. Final thickness should be around 1.5-2.5 mm. in 2 coats.
- 3 Smoothen the surface with fine Berger Wet & Dry Sheets 220 and remove loose particles after a minimum of 2 days of application of 2nd coat / final coat.
- 4 Apply a primer coat depending on the climatic conditions.
- 5 Apply 2 coats of Emulsion depending on the climatic conditions.

Special Note :

- Moisture content of the wall should be below 12%.
- pH value of the wall surface should be between 7-11.
- Mix well before use.

Storage :

- Store in a cool dry place.
- Keep away from source of ignition.
- Keep the bag sealed, out of children's reach and away from foodstuff.

Disposal :

- Do not pour left over putty down the drain or any watercourse.
- Dispose in accordance with local regulation.

Safety & Precaution :

- Do not over dilute or overextend.
- Do not apply on damp or high alkaline surfaces.
- Do not apply on chalking or flaking or cracked surface or where the surface is infected with fungus or algae.
- Do not apply if the ambient temperature is less than or expected to fall below 10°C.
- Allow sufficient time for each coat to dry before next coat application depending on ambient conditions.

Version No: BPP1/12/2024. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com