

PLATINA

WALMASTA PR300

WATER THINNABLE EXTERIOR AND INTERIOR PRIMER



PRODUCT INFORMATION



PLATINA Walmasta PR300 is a specially formulated value for money Primer 2-in-1 acrylic primer which can be used in both exterior & interior surfaces.

FEATURES AND BENEFITS

- **High Opacity** - Provides excellent opacity with fewer coats.
- **Resistant to Chalking** - Provides long-lasting finish with reduced surface powdering over time.
- **Easy Brushability** - Provides smooth, even coverage with minimal strokes.
- **Whiteness** - Provides excellent whiteness.
- **Green Pro Certified** - Validates our effort in striving towards to a sustainable future

USAGE

Suitable for Interior & Exterior.

PACK SIZE

Available in 20 ltrs.

COLOUR RANGE

White

SHELF LIFE

36 months from date of manufacture as long as the container is sealed and kept at normal temperature and away from direct sunlight

PHYSICAL & FILM PROPERTIES

Finish

Matt

Drying Time

Surface Dry : <30 min

Hard Dry : 4-6 hours

Depending on weather and surface conditions.

Flash Point

Non-flammable as it is water-based product

Version No: Walmasta PR300/01-06-2025. Please note that this data sheet supersedes all previous versions.

Berger Paints India Limited

Berger House, 129 Park Street, Kolkata 700017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030

Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com

Fire Hazard Class	Non-flammable
VOC Level	<50 gm/L
Viscosity	95 – 115 Ku
Coverage	1 COAT : 130 – 150 sq. ft/Lt* (by Brush Application) <i>(*Actual coverage may vary from the theoretical coverage due to factors such as method and condition of application, surface roughness, porosity and thickness of the film.)</i>

APPLICATION DATA

Application Method	By brush, roller, airless spray or conventional spray.
Recommended Dilution	Dilute 1ltr primer with up to 1ltr water depending on required consistency up to 100% (V/V).
Pot Life of Thinned Material	within 24 hrs
Recoating Period	Overnight drying, after applying first coat. <i>(Depending upon ambient temperature & humidity)</i>

DIRECTION FOR USE

Surface Preparation	1. Before painting, undertake repair of all surface imperfection, cracks, leakages, undulation.
Scrapping	2. Remove all loose paint, dirt, fungus, algae, moss and salt deposits by sanding the surface with Berger Sandpaper or alternatively by Berger Express Painting Sander with Paint Scraper attachment.
Crack Bridging	3. For filling cracks up to 5mm use Home Shield Crack Fill Paste. For wider cracks use Home Shield Advance Latex Plus as per the product usage guidelines.
Waterproofing	4. If required, apply Home Shield Latex Shield 2K on the affected areas as per the product usage guidelines. For highly affected areas Home Shield DampStop coating system is recommended.

PLATINA

WALMASTA PR300

WATER THINNABLE EXTERIOR AND INTERIOR PRIMER



Putty Application	Apply 2 coats of Bison Wall Putty with an overnight drying interval. For enhanced waterproofing, Home Shield Waterproof Putty is recommended.
Recommended Putty	Walls : HS Waterproof Putty/Bison Wall Putty/Acrylic Putty
Primer Application	Apply 1- 2 coats of PLATINA Walmasta PR300 Primer and allow 6-8 hours of drying time between coats.
Special Note	<ol style="list-style-type: none">1. Shake well before use and do not over dilute.2. Strain the material through a fine sieve before use.3. Moisture content of the wall should be below 12%.4. pH value of the wall surface should be between 7-11.

HEALTH, SAFETY & ENVIRONMENTAL SECURITY

Storage	<ol style="list-style-type: none">1. Store in a cool dry place.2. Keep away from source of ignition.3. Keep container tightly closed, out of children's reach and away from foodstuff.
Disposal	<ol style="list-style-type: none">1. Do not pour left over paint down the drain or any watercourse.2. Dispose in accordance with local regulation.
Safety & Precaution	<ol style="list-style-type: none">1. Ensure good ventilation during application and drying of paint.2. Wear protective clothes and gloves.3. Smoking is prohibited while painting.4. Avoid inhaling the vapour. Wear suitable dust nose pad when rubbing the surface.5. Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.

Version No: Walmasta PR300/01-06-2025. Please note that this data sheet supersedes all previous versions.

Berger Paints India Limited

Berger House, 129 Park Street, Kolkata 700017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030

Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com