



Product Attributes



Tough Film

Soft Sheen Finish



Excellent Washability

Anti-Fungal



Green Pro Certified

3 YEARS WARRANTY

LUXOL SATIN ENAMEL



Product Description

Luxol Satin Enamel is a solvent based anti-fungal, washable and long lasting paint. It offers an excellent sheen with a silken smooth, glowing finish and has excellent washable properties. It can be used on all types of metal, wood and masonry surfaces. It is ideal for use in rooms, kitchens, balconies and bathrooms. It has more longevity as it helps avoid mold growth, has better cleanability along with a soft sheen.

Recommended Use

Area of application:



Metal



Wood




Masonry

Suitable for:



For Interior & Exterior

Colour Range



8 Ready shades
&
5 Tinting Bases -
(P0/W3/N/Light Brown/Br. Yellow)
(More than 2000 shades
can be offered)

Finish

MATT

SOFT SHEEN ✓

HI-GLOSS

SUPER GLOSS

Recommended Dilution



Can be diluted with
Berger Thinner (T65/03E/800)

Brush/Roller application : 0 - 5% (V/V)
Spray application : 10 - 15% (V/V)

Application Method



Brush, Roller & Spray

Flash Point



Above 30°C

Drying Time



SD : 3 Hrs - 4 Hrs
(Depending on weather conditions)
HD : Overnight

Coverage



1 COAT : 180 - 200 sq.ft/Lt*
2 COATS : 100 - 120 sq.ft/Lt*
(by Brush Application)

(*Actual coverage may vary from the theoretical coverage
due to factors such as method and condition of application,
surface roughness, porosity and thickness of the film.)

Viscosity

Brush / Roller :

60-65 sec @ 30°C./Ford Cup B-4

Spraying :

40-45 sec @ 30°C./Ford Cup B-4

Sheen Level



33 +/- 3 at 60° GH
on glass plate when released

Recoating Period



After 24 hours of applying first coat
(Depending upon ambient temperature)

LUXOL SATIN ENAMEL



Packs Available



500ml 1L 4L 10L 20 L



Stability Of Thinned Paint

To be used within 24 Hours



Fire Hazard Class

Flammable



Shelf Life

3 year from date of manufacture as long as the container is sealed and kept at normal temperature and away from direct sunlight

Surface Preparation

Surface Inspection:



Before painting, the surface must be free of rust, dirt, oil and grease. Remove grease, oil and other contaminants by using Berger Thinner - 800/T65/03E

Scrapping:



Prepare the surface by scrubbing with wire Brush or Berger Sand Paper No. 150/180 to ensure the surface is clean and smooth. Wipe out thinner and make sure the surface is fully dry.

Crack Bridging:



Walls : For filling cracks, up to 5mm, use Home Shield Crack Fill Paste. For wider cracks use Home Shield Advance Latex Plus as per product usage guidelines.
Wood : Use Woodkeeper Fill-O-Dent to fill the cracks.

Putty Application :



Apply 1 or 2 Coats of Putty at an interval of 4-6 hours.

Recommended Putty :

Metal : Luxol Knifing Putty
Walls : HS Waterproof Putty / Bison Wall Putty / Acrylic Putty
Wood : Luxol Knifing Putty/Fill-O-Dent Putty

Primer Application :



Apply 1 or 2 coats of primer as per recommended time interval and dilution.

Recommended Primers :

Walls : BP Cement Primer ST/BP White Primer ST
Ferrous Surface : Red Oxide Primer / Butterfly AC Metal Primer / Zinc Yellow Primer / Luxol QD Primer / BP QD Primer
Non-Ferrous Surface : Bison Wash Primer followed by Zinc Yellow Primer / Luxol QD Primer / BP QD Primer
Wood : Parrot Wood Primer



Top Coat :

Apply 2 coats of Luxol Satin Enamel with recommended dilution ratio as finishing coat, with a drying time of 24 hours between the coats.

Storage

Store in a cool dry place.
Keep away from source of ignition.
Keep container tightly closed, out of children's reach and away from foodstuff.

Disposal

Do not pour left over paint down the drain or any watercourse.
Dispose in accordance with local regulation.

Safety & Precaution

Ensure good ventilation during application and drying of paint.
Wear protective clothes and gloves.
Smoking is prohibited while painting.
Avoid inhaling the vapour. Wear suitable dust nose pad when rubbing the surface.
Wear eye protector during application. In case of contact with eyes, rinse immediately with plenty of water.

Version No: BPP1/09/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 • CONSUMER RELATIONS MANAGER • Ph : 1800-103-6030
SMS BERGER to 56767 • Email : consumerfeedback@bergerindia.com • www.bergerpaints.com
Corporate Office : Plot No. : CF - 4 • Premises No. : 02-0173 • Action Area - IC • New Town • Kolkata 700 156