



# SILK GlamArt

## ITALIAN COLLECTION

### VELLUTO



## PRODUCT FEATURES



Pearlescent  
Velvet Effect



Easy to use



Durable

## DRYING TIME

Touch dry- 2 hours

Hard dry- 6-12 hours

## COVERAGE

50sq. ft per litre for 2 Coats

## DILUTION

No dilution needed

## PACK SIZE

1 LTR

## SHELF LIFE

24 months in original unopened  
seal packaging.

Inspired by Italian artistry, the Velluto collection is all about the richness of velvet. With the royal feel of the fabric and delicate metallic hints, this texture plays with light in unique ways, making any space the epitome of grace, glamor and art.

## Usage Areas:

Can be used in a modern, minimalist interior or in a more traditional, ornate setting as well.

## DIRECTIONS FOR APPLICATION:

### Surface Preparation:

Italian Decorative Primer should be diluted with 5-10% water. Apply one coat of the product evenly on a smooth and compact surface. If covering a previously colored surface, a second coat of the product may be applied.

### Design Application:

The Product can be applied as is or be tinted. The Product is ready to use. Ensure the base is perfectly smooth and free of crusts or impurities. Smoothen the surface with the blade of the stainless-steel trowel to perfection. Using the stainless-steel trowel, apply a first coat of the product. It is not necessary to create effects as the first coat will serve as a "base" for the second application. When the product is perfectly dry, apply a second coat of the product, this time making crossed trowel strokes to recreate "light/dark" effects, without leaving large accumulations of the product. When the product is perfectly dry, smooth the surface with the clean and dry stainless-steel trowel to further compact the product and make it velvety to the touch.

### Finish:



Velluto Gold (VE202)



Velluto Gold



Velluto Gold (VE099)



Velluto Gold (VE208)



Velluto Pearl (VE067)



Velluto Pearl (VE040)

### Safety Norms:

Store the product in original packaging at ventilated and dry places at temperatures between +8°C & 30°C. To avoid possible differences in tonality during application, the use of the same batch is recommended. Apply the product at temperatures between +8°C & 30°C. Avoid contact with eyes and skin. In case of contact, wash immediately and seek medical attention. Do not breathe powders, vapors or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

Version No: BPP1/06/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 • CONSUMER RELATIONS MANAGER • Ph: 1800-103-6030

SMS BERGER to 56767 • Email: consumerfeedback@bergerindia.com • www.bergerpaints.com

Corporate Office: Plot No. : CF - 4 • Premises No. : 02-0173 • Action Area - IC • New Town • Kolkata 700 156