



WEATHERCOAT ANTI DUSTT KOOL



Product Attributes



DPUR Technology

Exceptional dust resistance keeps your walls sparkling clean




Heat Reflective Nano Technology

Solar reflective index (SRI) > 110



All Weather Protection

Protects from Rain & Heat



Anti-algae & Anti-fungal protection

Provides long-lasting protection against fungus and algae on the walls



8 Years Warranty



Green ProCertified
Validates our effort in striving towards cleaner, more sustainable future.

Product Description

Weathercoat Anti Dust Kool is a high performing exterior paint with rich sheen. With unique DPUR feature it provides dust free walls with added 'Heat reflective Nano Technology'. The paint is engineered to resist chalking, flaking, fading, developing algae-fungal growth while keeping the walls cooler by reducing temperature upto 5 °C. Anti Dustt Kool keeps the walls painted fresh for a longer period of time with cooling benefits.

Recommended Use

Exterior plastered surfaces and concrete blocks

Colour Range



Over 2,000 shades

Finish



Rich sheen

Safe for Health



VOC - < 50 gm/lit

Coverage

60 -65 sq.ft/ lt/2 coats, under ideal test conditions.

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Recommended Undercoats

Primer: For wall/plastered surfaces – WeatherCoat Exterior Primer / Seal-O-Prime. Alternatively use Home Shield Waterproofing Primers.

Putty: For wall/ plastered surfaces – Bison Wall Putty or HS Waterproof Putty

Drying Time



SD: 30 min depending on weather conditions

HD: 4-6 hours

Dilution Ratio



Brush/Roller: 400 ml of water per 1L of emulsion. In case of N Base shades, no dilution is advised to ensure proper colour depth

For dark shades only: Maximum dilution should be 10% depending on shade.

Application Method



Brush/ Roller/ Spray

Gloss Level



6-8 at 60° GH when released



WEATHERCOAT ANTI DUSTT KOOL



Packs



ColorBank/ Non-ColorBank – Pack



Fire Hazard Class
Non- flammable

Unusual Fire & Explosion Hazards

Material can splatter above 212°F.
Polymer film can burn.



Pot Life of Thinned Material
Within 24 hrs.

Health & Safety

If the paint comes in contact with eyes or skin, flush with a large amount of water for at least 15 minutes. See a physician, if irritation persists. Wash affected skin areas with soap and water.

Surface Preparation

For Previously Painted Surfaces:



Strip all the old paint and remove all the loose dust, grease, fungus and algae by sanding or wire brushing.



Cracks, holes, dents and damp areas should be repaired properly before painting.



Treat the surface with Bio-wash solution and wash it next day with potable water. Leave the surface to dry thoroughly.

For fresh/new surfaces:

The surface should be allowed to cure properly.

Primer Coat Application: Apply 1-2 coats of Recommended Primer as per product usage guideline. For best results use Waterproofing Primer.

Top Coat Application

Dilute the paint as per the recommended dilution ratio. Apply 2 - 3 coats of topcoat paint with 4 – 6 hours of interval after each coat.

Special Note

Before painting, the following things should be checked thoroughly:

- Ideal moisture content of the wall should be below 12%
- Ideal pH value of the wall surface should be between 7-11

Points to Note

- Shake well before use and do not over dilute or over extend brush
- Stir and strain the material through a fine sieve before use
- Do not apply on high alkaline surface
- Do not apply paint on a wet surface
- Do not apply paint on chalking or flaking surface or where the surface is infected with fungus / algae
- Do not apply paint if the ambient temperature is less than or expected to fall below 10°C
- Keep out of reach of children and away from foodstuff
- In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/01/2026. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com