



## Product Attributes



10 Years Performance Warranty

### Elastomeric Property

Covers hair line cracks upto 2 mm and prevents rainwater ingress



**Water Repellence**  
Silicon additives provides protection from Heavy rains

### Superior Dust Pick Up Resistance

Polymer composition doesn't allow dust to settle on the surface



### High Sheen

Sheen finish enhances the beauty of the house

### Anti Algal & Anti Fungal

Prevents the growth of algal & fungal for longer period



### Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future.



# WEATHERCOAT LONG LIFE FLEXO




## Product Description

High-performance exterior paint Weathercoat Long Life Flexo comes with elastomeric property that covers hairline cracks upto 2 mm and prevents rainwater ingress. It's Silicon additives offer protection against heavy rains and unique polymer composition prevents dust from settling on the exterior surface and inhibits growth of fungus and algae. This paint gives a high sheen finish to the walls and comes with an 10-year warranty.

## Recommended Use


Exterior plastered surfaces, concrete blocks and asbestos

### Colour Range



Over 2,000 shades

### Finish



High Sheen

### Safe for Health



VOC <50 gm/ltr  
No added Lead, Arsenic, Chromium (VI) and Mercury

## Coverage

70 -75 sq.ft/ lt/2 coats, under ideal test conditions.

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

## Recommended Undercoats

**Primer:** For wall/plastered surfaces – Use Seal o Prime or Waterproofing primer coat : Damp Stop Duo or Damp Stop Elasto or PU RoofKoat

**Putty:** For wall/plastered surfaces – Bison Wall Putty or HS Waterproofer Putty

### Drying Time



SD: 30 min depending on weather conditions

HD: 4-6 hours

### Dilution Ratio



**Brush/Roller:** 400 ml of water per 1L of emulsion. In case of N Base shades, no dilution is advised to ensure proper colour depth

**For dark shades only:** Maximum dilution should be 10% depending on shade.

### Application Method



Brush/ Roller/ Spray

### Gloss Level



14-18 at 60° GH when released



## Packs



ColorBank/ Non-ColorBank – Pack



### Fire Hazard Class

Non- flammable

### Unusual Fire & Explosion Hazards

Material can splatter above 212°F.  
Polymer film can burn.



### Pot Life of Thinned Material

Within 24 hrs.

### Health & Safety

If the paint comes in contact with eyes or skin, flush with a large amount of water for at least 15 minutes. See a physician, if irritation persists. Wash affected skin areas with soap and water.

# WEATHERCOAT LONG LIFE FLEXO



## Surface Preparation

### For Previously Painted Surfaces:



Strip all the old paint and remove all the loose dust, grease, fungus and algae by sanding or wire brushing.



Cracks, holes, dents and damp areas should be repaired properly before painting.



Treat the surface with Bio-wash solution and wash it next day with potable water. Leave the surface to dry thoroughly.

### For fresh/new surfaces:

The surface should be allowed to cure properly.

**Primer Coat Application:** Apply 1-2 coats of Recommended Primer as per product usage guideline. For best results use Waterproofing Primer.

## Top Coat Application

Dilute the paint as per the recommended dilution ratio. Apply 2 - 3 coats of topcoat paint with 4 – 6 hours of interval after each coat.

### Special Note

Before painting, the following things should be checked thoroughly:

- ▶ Ideal moisture content of the wall should be below 12%
- ▶ Ideal pH value of the wall surface should be between 7-11

### Points to Note

- ▶ Shake well before use and do not over dilute or over extend brush
- ▶ Stir and strain the material through a fine sieve before use
- ▶ Do not apply on high alkaline surface
- ▶ Do not apply paint on a wet surface
- ▶ Do not apply paint on chalking or flaking surface or where the surface is infected with fungus / algae
- ▶ Do not apply paint if the ambient temperature is less than or expected to fall below 10°C
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help

Version No: BPP1/01/2026. Please note that this data sheet supersedes all previous versions.

## BERGER PAINTS INDIA LIMITED

**Berger House**, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com