

KOLOR PLUS GLOW

Interior Premium Emulsion



Features



Washable

Glowing
Finish



Anti-Fading

6 years of
Warranty



High
Coverage/
High Opacity

Product Description

Kolor Plus Glow is a premium interior emulsion designed with European technology to maintain vibrant, glowing walls for years. With Color Guard Technology, it delivers durable colour and a rich, smooth finish, along with easy washability for lasting freshness.

Recommended Use

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling



Coverage

120-140 sqft/ltr/2 coats depending on shade, quality of surface preparation and application condition.



VOC

VOC- 5 gm/ lit (max)



Recommended Dilution

Brush application: 50% by volume.
Auto-roller/ spray: 50% by volume.
Deep shades from the N2 base are to be applied without dilution



Drying Time

Surface Dry: 15-25 min at 60% RH, 25°C **Hard Dry:** 6-8 hours



Gloss/Sheen

Soft Sheen

KOLOR PLUS GLOW

Interior Premium Emulsion



Packs



1 Ltr

4 Ltr

10 Ltr

20 Ltr



Stability of Used Paint
Use within 24 hrs

Surface Preparation



For fresh/ new surfaces, ensure the surface is clean and dry and free from all loose particles, chalk, grease, fungus and algae. Sand the surface with Emery Paper No. 80 and wipe clean. Apply one coat of bio-wash after cleaning fungal / algal growth.



Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty / cement to dry.



Apply the first coat of primer and allow it to dry for 6 – 8 hours.



Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight.



Sand the surface with Emery Paper No. 100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 – 8 hours. Sand the surface with Emery Paper No. 220 and wipe clean.



For Previously Painted Surfaces

Strip the old paint as far as possible. Roughen the unremoved portion with no 180 or no 220 emery paper. Remove all loosely adhering particles or dust.



Directions for Application

For topcoat, dilute the paint as per the recommended dilution ratio. Apply the first finishing coat with brush or roller and allow it to dry for at least 6 -8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

Points to Note

- Shake well before use
- Do not over dilute.
- Keep the container tightly closed to prevent drying
- Use one coat of Bio – Wash for killing fungal growth
- Scrape off old paint thoroughly before painting starts
- Gyro shake well after tinting through CB Machine
- For deep shade apply one additional coat
- Do not apply paint on lime washed surfaces and damp wall
- In case of contact with eyes, wash immediately with water and seek medical help
- Do not apply paint when ambient temperature is below 10°C or above 45°C

Version No: BPP1/03/2026. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com