

TANK KOOL

HEAT RESISTANT COATING

BERGER
(HOME)
SHIELD
WATERPROOFING SPECIALIST



Product Description

Tank Kool is a high performance functional exterior painting system specially designed for application on plastic water storage tank. This coating system is capable to cool down temperature of the stored water to a large extent. This can also be applied over corrugated metal roof sheet, concrete etc. to get cooling effect. This painting system comes in a combo pack with the following:

- Primer
- Mid coat
- Clear top coat

Recommended Use

Suitable for plastic water storage tank, corrugated metal roof sheet, concrete, asbestos etc.

Product Attributes



Solar reflection


Temperature
reduction
up to 10°



Maintenance
Free



Applicable for
Exposed Pipes



Drying Time



Surface dry: 20-30 minutes for primer and 30-45 minutes for mid coat and 10-15 minutes for top coat ;
Hard dry: over night for primer; 6-8 hours for the mid coat; 2-3 hours for top coat

Toxicity



VOC: <520 gm/Lit for primer; <50 gm/Lit for mid coat and < 700 gm/Lit for top coat

Recommended Dilution



No dilution to be applied as such

Coverage



One full combo pack for 1KL tank

Over coating interval



Overnight

Gloss at 60° GH



5-6 measured as per standard method

Application Tools




Brush

TANK KOOL

HEAT RESISTANT COATING



Packs



Shelf Life
18 Months

Surface Preparation



Surface preparation: Ensure the plastic or metal surface is free from dust, grease, iron deposits, rust etc. by proper sanding. Concrete should be fully cured and ensure it is free from loose / chalky materials, fungus, algae etc. Cracks, holes, dents, damp areas etc. should be repaired properly before painting and surface should be treated with Biowash solution if required



Priming: Apply one coat of this solvent based Primer and allow to dry for overnight.

Mid Coat: Apply one coat of water based Mid coat allow to dry completely.

Top Coat: Apply one coat of solvent based Clear coat.

Precautions

- Stir well before use.
- Do not dilute or over extend brush.
- Do not apply paint on high alkaline surface.
- Do not apply paint on wet surface.
- Do not apply paint on chalking or flaking surface or where the surface is infected with fungus or algae.
- Do not apply paint if the ambient temperature is less than or expected to fall below 10°C.
- Allow sufficient time for each coat to dry before next coat application.

Safety Data

Refer SDS for safety precautions.

Storage

Store the container in a cool, dry place with the lid tightly closed in an upright position.

Additional Information

No added lead, Chromium (VI), Mercury.

Note

- Best practice would be to use separate brushes for each coat.
- This product is not recommended on lime wash.

Version No: BPP1/04/2025. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com